

FARMTRAC FT26




**24.4hp
diesel
engine**

Compact design and unmatched versatility

The FT26 and FT26HST are ideal for multiple applications, such as greenhouses, smallholdings, paddocks or orchards. Powered by a 24.4hp Mitsubishi diesel engine with selectable 4WD and available with a 9x3 manual transmission or a 3-range HST transmission.

There's an abundance of versatility with the FT26 models.

FARMTRAC

FT26

ENGINE	FARMTRAC FT26	FARMTRAC FT26H
ENGINE HP	24.4	24.4
NO. OF CYLINDERS	3	3
TYPE	NATURAL ASPIRATED	NATURAL ASPIRATED
VOLUME (CC)	1318	1318
PTO		
REAR PTO (RPM)	540 & 540E	540
MID PTO (RPM)	N/A	2000
TRANSMISSION		
TYPE	9F+3R CONSTANT MESH	3-RANGE HST
DIFFERENTIAL LOCK	STANDARD	STANDARD
BRAKES		
TYPE	OIL IMMERSED BRAKES	OIL IMMERSED BRAKES
PARKING BRAKE	INDEPENDENT	INDEPENDENT
THREE POINT LINKAGE		
CATEGORY	CAT 1N	CAT 1N
STAY BAR/CHECK CHAIN	BOX TYPE STAY BAR	BOX TYPE STAY BAR
HYDRAULICS		
REAR LINKAGE CONTROL	DRAFT AND POSITION CONTROL	POSITION CONTROL
LIFT CAPACITY (KG)	750KG (AT HITCH POINT)	750KG (AT HITCH POINT)
AUXILIARY VALVE	1DA (2 NOS.)	1DA (2 NOS.)
STEERING		
TYPE	HYDROSTATIC POWER STEERING	HYDROSTATIC POWER STEERING
FRONT AXLE		
TYPE	SELECTABLE 4WD	SELECTABLE 4WD
CAPACITIES		
FUEL TANK (LTRS)	24	24
DIMENSIONS		
LENGTH (MM)	2465	2465
WIDTH (MM)	1040	1040
HEIGHT (MM)	2192 UP TO BEACON	1960 TO ROPS
WHEELBASE (MM)	1550	1550
GROUND CLEARANCE (MM)	310	265
WEIGHT (KG)	1000	1050



LOGICALLY LAID OUT CONTROLS



INDEPENDENT HST PEDALS



REAR THREE POINT LINKAGE

STANDARD EQUIPMENT

- 24.4HP MITSUBISHI DIESEL ENGINE
- SELECTABLE 4WD
- POWER STEERING
- REAR HYDRAULIC SPOOL VALVES
- FOLDING ROPS
- EASY TO VIEW INSTRUMENT PANEL
- REAR WORK LAMP
- ROAD LIGHTING KIT
- FLASHING BEACON (ROPS MOUNTED)
- BATTERY ISOLATOR
- REAR MOUNTED TOOL BOX
- 2 X 15KG FRONT WEIGHTS

OPTIONAL EQUIPMENT

- AGRICULTURAL TYRES
- TURF TYRES
- INDUSTRIAL TYRES
- 3000 SERIES FRONT LOADER
- LOADER 3RD FUNCTION KIT

Specifications correct at time of publishing but are subject to change at any time.